

# AMG510-4G-24S-4XS










## 32 PORT LIGHT INDUSTRIAL MANAGED LAYER 2+ SFP SWITCH



## Light Industrial Ethernet Solutions

AMG's fully managed layer 2+ Ethernet switches provide 100Mbps, Gigabit and 10 Gigabit Ethernet switching for light industrial network applications. Available with 4x RJ45 Gigabit ports, 24x 100Mb/Gigabit SFP ports and 4x 1/10 Gigabit SFP+ ports.



 Gigabit x4	 100/1000 x24	 1/10 Gb x4	 Managed Full	 Secure 802.1x	 Temp -10--+60°C	 Mounting Rack/Surface	 PSU AC & DC	 NDA/TAA Compliant
---	---	---	---	--	--	--	--	--

[ AMG510-4G-24S-4XS ]

### OVERVIEW

AMG510 series layer 2+ managed Ethernet switches are designed for 19inch rack or desktop mounting within light industrial or commercial applications. The AMG510-4G-24S-4XS has 4 Gigabit Ethernet RJ45 ports, 24 100Mb/Gigabit SFP ports and an additional 4 multi-rate SFP+ ports providing 100Mb, 1Gb, 2.5Gb or 10Gb speeds for data uplink into core networks, providing application and site flexibility.

Support for the latest in security features ensure that the AMG510 series can provide robust security and reliability as part of an overall secure network design strategy.

The AMG510 series support a wide range of management functions as well as Rapid Spanning Tree Protocol (RSTP), Multiple Spanning Tree Protocol (MSTP) and Ethernet Ring Protection Switching (ERPS) for network redundancy. IGMP functionality is supported to handle the multicast traffic which is commonly used in IP CCTV deployments.

SFPs need to be ordered separately.

### FEATURES

- 19inch 1U rack or desktop/shelf mount
- -10°C to +60°C temperature maintains performance in challenging environmental conditions
- Dual redundant power supply inputs as standard - 1x AC Mains + 1x Low Voltage DC
- Compliant with all IEEE 802.3 speeds (i/u/ab/z/ae)
- Dual Speed SFP or SFP+ ports (up to 10Gb Speed)
- Supports RSTP, MSTP, ERPS, SNMP v1-3 and IGMP v1-3
- Port trunk functionality available with LACP
- IEEE 802.1x port security enabled
- Supports 9.6K bytes jumbo frames
- Layer 3 Static Routing
- AMG 3 Year Support Warranty

# Specifications.

## Standards.

IEEE 802.3i	10Base-T
IEEE 802.3u	100Base-TX & 100Base-FX
IEEE 802.3ab	1000Base-T
IEEE 802.3z	1000Base-X
IEEE 802.3ae	10GBase-R
IEEE 802.3x	Flow Control
IEEE 802.3ad	Port Trunk with LACP
IEEE 802.3az	Energy Efficient Ethernet
IEEE 802.1D	Spanning Tree (STP)
IEEE 802.1w	Rapid Spanning Tree (RSTP)
IEEE 802.1s	Multiple Spanning Tree (MSTP)
IEEE 802.1p	QoS Priority Marking
IEEE 802.1Q	VLANs
IEEE 802.1v	VLAN Classification
IEEE 802.1X	Port Security
IEEE 802.3AB	LLDP
RFC1112, 2236, 3376, 4604, 5711	IGMP v1, v2, v3
RFC2236, 3376	IGMP Snooping
RFC8907	TACACS
RFC2865, 2866	RADIUS
RFC5424	Syslog
RFC4250 - 4254	SSH
RFC5246	TLS1.2 / HTTPS
RFC854	Telnet
RFC2030	SNTP
RFC2131	DHCP
ITU-T G.8032	Ethernet Ring Protection Switching (ERPS)

## Hardware Features.

Architecture	Store-and-Forward
Switch Latency	<7µs
Switch Fabric	136Gbps
Address Table	32K MAC Entries
Buffer Memory	32M bits
Jumbo Frames	9.6K bytes
CPU	400MHz
SDRAM	128Mb
Flash	16Mb
VLAN's	4K
IGMP Groups	1024
IPv6 MLD Groups	1024
Throughput	101.18Mpps @ 64bytes
Priority Queues	8
Bandwidth Control	Ingress Packet Filter and Egress Rate Limit

## Layer 3 Features.

Static Routing:	
Interfaces	128 Max
Routes	128 Max
DHCP	Server (IPv4)

## Software Features.

Redundancy	STP RSTP MSTP ERPS (G.8032)
VLAN	802.1Q Port Based VLAN Private VLAN Voice VLAN Multicast VLAN Registration Dynamic Trunk Static Trunk DDM
MVR LACP	
SFP Monitoring GARP/GVRP	
IGMP Snooping IGMP Querier	v1/v2/v3 (128 VLAN's Max)
MLD Snooping MLD Querier	IPv6 (128 VLAN's Max) IPv6
IPMC	64 Profiles (128 Rules Each)

## QoS.

Class of Service	802.1p QoS & DSCP
Diffserv	RFC2474
Rate Limiting	Ingress / Egress
Priority Queue	WRR / Strict / Hybrid Priority

## Security.

Port Security	MAC/IP Based
Storm Control	Rate Limiting
802.1x	RADIUS Authentication
TACACS+	
HTTPS/SSL	
BPDU Guard	
DHCP Snooping	
Loop Protection	
IP Source Guard	IPv4 & IPv6
IP Authorisation Managers	
Manufacturer OUI Port Security	
Access (Policy) Control List (ACL L2/3/4)	
Custom User Rights	15 Levels (20 Users Max)

# Specifications.

## Management.

DHCP	Client / Relay (IPv4 & IPv6) Option 66/67/82
Event/Error Log	Syslog Client
Management Access	SNMP Web GUI Telnet / SSH v2.0 / CLI
Access Management	Filtering
SNMP	v1/v2c/v3
RMON	1/2/3/9 Groups
Port Mirroring	
Software Update	HTTP/HTTPS
Config Export /Import	
Dual Firmware Images	
SNTP	Client (IPv4 & IPv6)
Configuration	IPv4 & IPv6
LLDP	Link Layer Discovery Protocol
LLDP-MED	
Time Zone & Daylight Savings	
sFlow	
Cable Diagnostics	

## Interface.

LED Indicators	1x Power SFP Link/Activity SFP Speed RJ45 Link/Activity RJ45 Speed SFP+ Link/Activity
RJ45 Ports	4x 10/100/1000T(X) RJ45 with Auto MDI/MDI-X
SFP Slot	24x 100/1000FX SFP
SFP+ Slot	4x 100M/1G/2.5G/10G SFP+
Power:	
AC Input	1x IEC C14 Socket
DC Input	1 x 2 pin Removable Terminal
Serial Console	RJ45

## Power.

Power Inputs	2 (1x AC + 1x DC Redundant)^
Operating Voltage:	
Mains	90-264V <sub>AC</sub>
DC	12-48V <sub>DC</sub>
Power Consumption	50 Watts Max
Redundant Mode	AC Primary / DC Secondary

^ DC Power Supply Sold Separately

## Packaging.

Shipping Weight	4kg / 8.82lb
Dimensions	(W x D x H) 500 x 310 x 91 mm 19.68 x 12.20 x 3.58 in

## Mechanical.

Housing	Metal
Dimensions:	(W x D x H) Excluding 19inch Brackets 440 x 220 x 44 mm 17.32 x 8.66 x 1.73 in
IP Rating	IP20
Installation	19inch Rack (1U) or Desktop
Weight	3.1kg / 6.83lb

## Environmental.

Operating Temp.	-10 to +60°C / 14 to +140°F
Storage Temp.	-20 to +85°C / -4 to +185°F
Humidity	5% to 90% (non-condensing)
MTBF	236,109 hours
MTBF Standard	MIL-HDBK-217F GF
Heat Dissipation	170 BTU/h (with Max Load)
Cooling	2x Cooling Fans (Temp. Controlled)
Airflow	Front to Back
Noise Level	58 dBA

## Regulatory.

Safety	IEC/EN 62368-1
EMI	EN55032 Class A CISPR 32 FCC Part 15B Class A
EMS	EN61000-4-2 (ESD) EN61000-4-3 (RS) EN61000-4-4 (EFT) EN61000-4-5 (Surge) EN61000-4-6 (CS) EN61000-4-8 (PFMF) EN61000-4-11 (Dips)
Environmental	Reach RoHS WEEE
Supply Chain	NDAA & TAA Compliant

# Part Numbers.

---

## 10Gb Light Industrial Layer 2+ Managed Switches

AMG510-4G-24S-4XS	4 × 10/100/1000TX, 24 × 100/1000FX SFP & 4 × 100M/1G/2.5G/10G SFP+
-------------------	--

## Recommended PSUs.

---

For Dual PSU Use	AMGPSU-I12-P54	12V <sub>DC</sub> 4.5A, 54W PSU, DIN rail mount (only required if dual PSU input operation is desired)
------------------	----------------	--

## Notes.

---

Included Accessories:	19inch Mounting Brackets, 4x Rubber Feet, Console Cable, Region Specific Line Cord
Optional Accessories:	SFP/SFP+ modules - Optical/Copper see separate list, need to be ordered separately

*In a continuing effort to improve and advance technology, product specifications are subject to change without notice. Please visit [www.amgsystems.com](http://www.amgsystems.com) for the latest product specifications.*